The University of Florida Water Institute



□ 1 Introduction

Florida Water and Climate Alliance

A Stakeholder-Scientist Network





Goal: To increase the regional relevance and usability of climate and sea level rise models for the specific needs of water suppliers and resources managers in Florida.

1 Introduction

Tampa Bay Water Project Objectives

- Evaluate the ability of Global Climate Models (GCMs) to reproduce retrospective temperature and rainfall in the Tampa Bay Region
- Evaluate the ability of GCMs to reproduce retrospective hydrologic behavior when used with the calibrated Integrated Northern Tampa Bay (INTB) Model
- Evaluate changes in hydrology resulting from GCM future climate projections
- Quantify the relative uncertainties of changes in future climate and water use scenarios for water supply planning

02

Methods and Materials

8 GCMs (CMIP5, RCP8.5)¹ 8 Water use scenarios

3 ET₀ estimation Methods¹

(Hargreaves, Penman-Monteith, Priestly Taylor)




Retrospective period: 1982-2005

Future period 1: 2030-2060 Future period 2: 2070-2100

Changes in hydrology, changes in environmental compliance, ability to meet future demand.


- Historic climate data: NLDAS-2 (1/8th degree grid)
- Hydrologic model: Integrated Hydrologic Model (IHM)
- Study region: Integrated Northern Tampa Bay (INTB)



Ref: ¹Chang et al (2016)

02

Methods and Materials



Variance-based GSA and Tukey's HSD test to evaluate statistical differences in changes in e nvironmental compliance, ability to meet future demand.

Ref: ¹Hwang & Graham (2013)



Methods and Materials

Bias Correction Stochastic Analog (BCSA) Downscaling Technique¹

What we did

Developed a new statistical downscaling method (BCSA) and compared it to existing methods (BCSD, SDBC, BCCA)

Why we did it

Existing statistical downscaling methods did not reproduce spatiotemporal rainfall characteristics in Florida well

What we found...


Choice of statistical downscaling method matters in Florida!

Note: Even dynamic downscaling requires bias correction before use in hydrologic models!




Results: Comparison of Downscaling Methods


Wet season average daily rainfall



Wet season standard deviation of daily rainfall




Wet season frequency of wet spells >5 days



03


Results: Comparison of Downscaling Methods

Wet season spatial structure



$03\frac{}{\text{Results}}$

Comparison of raw and downscaled, bias-corrected retrospective P and ET₀




All GCMs must be bias corrected before use with IHM!!




 $02 \frac{1}{\text{Methods}}$


Integrated Hydrologic Model (IHM)



$03\frac{}{\text{Results}}$

Comparison of retrospective monthly streamflow predicitions






Retrospective streamflow OK after P and ET₀ bias-correction

Results

Projected future monthly change in P, ET₀ and (P-ET₀)



2045 Water Use Scenarios: Demand Assumptions

- Tampa Bay Water Urban demand projected to be ~280
 MGD in 2045 assuming active water conservation.
- Climate-driven agricultural irrigation water demand estimated by the AFSIRS model using GCM future projections
- Land use change not considered. Increases in demand assumed to be the result of intensification on existing lands


2045 Water Supply Scenarios

	Groundwater Pumping for Retrospective Climate (MGD)					
Scenario	Irrigation Demand	Agricultural Pumping ¹	Urban Pumping ² (CWF) ³	Total GW Pumping		
No groundwater pumping	0	0	0	0		
No urban groundwater pumping	163	192	0	192		
No agricultural groundwater pumping	0	0	356(90)	356		
Agricultural adaptation (25% GW reduction) ⁴	129	152	356(90)	508		
Business as Usual	163	192	356(90)	548		
Increase agricultural demand (25% GW increase) ⁴	203	239	356(90)	595		
Increase CWF groundwater pumping (45%)	163	192	396(130)	588		
Increase all urban groundwater pumping (45%)	163	192	514(130)	706		

- ¹Agricultural = agricultural & recreational
- ²Urban = public water supply & industrial
- 3CWFs: Consolidated wellfields
- ⁴reduction/increase over climate driven demand

$03\frac{}{\text{Results}}$


Retrospective versus future mean daily streamflow (Business as usual scenario, Hargreaves ET)



Lower mean streamflow in summer months. Future 2 < Future 1. Large spread in future projections!

$03 \frac{1}{\text{Results}}$

Retrospective versus future mean daily groundwater level (Business as usual scenario, Hargreaves ET)





Global Sensitivity Analysis

The first order sensitivity index of change in streamflow


River gage	Season	Period	GCM	ET	Scenario
Hillsborough	Wet season	Fut1	0.944	0.002	0.016
		Fut2	0.930	0.041	0.006
	Dry season	Fut1	0.948	0.012	0.029
		Fut2	0.961	0.001	0.018
		1			†
GCM is dominant cause of spread in projections			ET and Water Use Scenario low		



Global Sensitivity Analysis

The first order sensitivity index of change in groundwater level


GCM and water use scenario are both significant sources of spread



\bigcirc Results


Change in available water from the Hillsborough River

By water use scenario



By GCM

5 GCMs projected decrease



When averaged over water use scenarios and ET method, Differences among GCMs are statistically significant




Change in percent of the time that GW is above target level

By water use scenario


Reduction in municipal pumping leads to increase in time GW is above target at this well

By GCM



Differences among GCMs are statistically significant

Scenario Discovery Analysis¹: Ability to meet Tampa Bay Water projected 2045 demand and meet environmental regulations



- Meets 2045 demand and maintains compliance with groundwater regulations
- Meets 2045 demand but does not maintains compliance with regulations
- Does not meet 2045 demand but maintains compliance with regulations
- Does not meet 2045 demand or maintains compliance regulations



Take home messages

- Downscaling technique matters! Even dynamically downscaled GCMs must be bias corrected.
- Projected changes in streamflow and groundwater level vary depending on choice of GCM, ET method, water use scenario and RCP scenario
- The uncertainty attributed to GCMs was the dominant factor influencing different future streamflow projections.
- The uncertainty attributed to GCM and water use scenario both contributed to significant differences in future groundwater level projections.
- For three ET methods shown here uncertainty relatively small.
- Climate models projected significantly different changes in streamflow and groundwater. 5 to 6 GCMs among 8 projected decreases in water availability.
- Even with active conservation and dramatic increases in use of reclaimed water current regulations on water withdrawals may have to adapt to future climate.



Thank you





Evapotranspiration Method Selection

What we did

 Evaluated uncertainty in P, T, and ET₀ projections using Global Sensitivity Analysis and Monte Carlo Filtering

Why we did it

 To develop an appropriate ensemble of GCMs, ET methods and RCP trajectories for evaluating future climate change

What we found

- Choice of ET method matters!
- Evaluate impacts of future projections over an ensemble of GCMs and a variety of ET methods and RCP trajectories

2070-2100 Change in Annual P-ET₀ by ET method (averaged over GCMs and RCPs)

